



# 200 Watt Medical Series

Desktop Type



ATM200 - P X X X

P : C6 / C14 ← O / P Voltage →

### Green Mode

Meet CEC , Energy Star Level V , ErP Stage 2  
NO Load Power Consumption Less Than 0.5W

### Features :

- ANSI/AAMI/IEC/EN ES60601-1:2005 (60601 3rd edition)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current : < 100µA
- 100-240VAC Universal Input
- Single Output to 200W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 2 Years Warranty

### Output

Load Regulation	±5% ( Typical )
Ripple	1 ~ 2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	16AWG
Ferrite Core	NO( Optional )

### Safety Approvals

CB / UL / cUL / FCC / CE / T-mark(TUV) / PSE

Model	O/P Voltage	O/P Current	Watt
ATM200-P120	12.0V	16.00A	192.00W
ATM200-P180	18.0V	11.00A	198.00W
ATM200-P190	19.0V	10.50A	199.50W
ATM200-P240	24.0V	8.30A	199.20W
ATM200-P480	48.0V	4.17A	200.16W

### Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.5A-0.9A
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6, C14

### Electrical

Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	Energy Star Level V , ErP Stage 2 Certified
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2
EMS Immunity	Compliance to IEC60601-1-2
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

### Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	L 204 × W 81 × H 42.5 (mm) ( Ref. )
Weight	880 g ( Ref. )