

SPU45 series

50W Desk Top Type
I.T.E. Power Supplies

Features:

- Wide Operating Voltage 90 to 264 VAC, 47 to 63 Hz
- IEC-320-C14 Input Inlet
- Optional Output Connector (See page appendix)
- Over Voltage Protection (Crowbar Design)
- Input Surge Current, Over Voltage And Over Load protection
- Single to Triple Output
- Class I
- 3 year warranty



Electrical Characteristics:

Vin	Safety Approvals Input Voltage Range	100~240VAC
	Operate Voltage Range	90~264VAC
fin	Input Frequency	47~63Hz
Po	Output Power Range	See rating chart
Vo	Output Voltage Range	See rating chart
Io	Output Current Range	See rating chart
Iil	Input Current (Low Line)	Io=Full load, Vin=100VAC 1.35A
Iih	Input Current (High Line)	Io=Full load, Vin=240VAC 0.80A
Ir	Low Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=115VAC 20A (max.)
	High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC 40A (max.)
Eff	Efficiency	Io=Full Load, Vin=230VAC 70~88%
REG-i	Line Regulation	Io=Full Load 0.5~1%
REG-o	Load Regulation	Vin=230VAC 3~7%
OVP	Over Voltage Protection	112~132%
OCP	Over Current Protection	110~150%
Ttr	Time of Transient Response	Io=Full Load to Half Load, Vin=100VAC 4mS (max.)
Th	Hold-Up Time	Io=Full Load, Vin=110VAC 12mS (min.)
Ts	Start Up Time	Io=Full Load, Vin=100VAC 3S (max.)
Vp-p	Ripple & Noise(Peak to Peak)	Full Load, Vin=90VAC 1% (max.)
Ilk	Safety Ground Leakage Current	Vin=240VAC/60Hz 0.75mA (max.)
TC	Temperature Coefficient	All output ±0.04%/°C
Pno	No-Load Power Consumption	No load, Vin=230VAC See rating chart
Vps	Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary 4242VDC (min.)
Vpg	Dielectric Withstanding Voltage for Primary to PE	Primary to PE 2677VDC (min.)
Ris	Isolation Resistance	Test Voltage=500VDC 50MΩ (min.)

Note: The Ripple & Noise which is under 3.3VDC at 2% max, Allowed OVP Range 112~150%.

Environmental

To	Operating Temperature	See derating curve
Ts	Storage Temperature	-40~85°C
Ho	Operating Humidity	0~95%
Hr	Storage Humidity	0~95%
MTBF	Operating Temperature at 25°C, Calculated per MIL-HDBK-217F	0.1M Hrs (min.)
Pd	Derate linearly from 100% load at 40°C to 50% load at 70°C	

Application:

- POS System
- AV Equipment
- Industrial PC
- Note PC
- Charger
- LED Lighting

Safety Approvals:

cULus CB CE FC



UL/c-UL(UL 60950-1:2nd Edition)
TUV/GS(EN 60950-1:2nd Edition)



SPU45 series

50W Desk Top Type
I.T.E. Power Supplies


Output Voltage And Current Rating Chart (Single Output) :

Model Number	Output Voltage	Output Current	Total Regulation	Max. Output Power	Pno (max.)
SPU45-101	3 ~ 5 VDC	8.00 A max	5%	40W	4W
SPU45-102	5 ~ 6 VDC	8.00 ~ 6.66 A	5%	42W	4W
SPU45-103	6 ~ 8 VDC	7.00 ~ 5.25 A	5%	42W	4W
SPU45-104	8 ~ 11 VDC	5.63 ~ 4.00 A	5%	45W	4W
SPU45-105	11 ~ 13 VDC	4.00 ~ 3.46 A	5%	45W	4W
SPU45-106	13 ~ 16 VDC	3.46 ~ 2.81 A	5%	45W	4W
SPU45-107	16 ~ 21 VDC	3.12 ~ 2.38 A	5%	50W	4W
SPU45-108	21 ~ 27 VDC	2.30 ~ 1.85 A	3%	50W	4W
SPU45-109	27 ~ 33 VDC	1.85 ~ 1.51 A	3%	50W	4W
SPU45-110	33 ~ 40 VDC	1.51 ~ 1.25 A	3%	50W	4W
SPU45-111	40 ~ 50 VDC	1.25 ~ 1.00 A	3%	50W	4W

Output Voltage And Current Rating Chart (Multi Output) :

Model Number	Output #1				Output #2				Output #3				Max. Output Power	Pno (max.)
	Vonom	Iomin	Iomax	Regmax	Vonom	Iomin	Iomax	Regmax	Vonom	Iomin	Iomax	Regmax		
SPU45-200	+3.3V	0.5A	5A	7%	+12V	0.3A	2A	5%					40W	4.5W
SPU45-201	+5V	0.5A	5A	5%	+12V	0.3A	2A	5%					42W	4.5W
SPU45-202	+5V	0.8A	5A	7%	+15V	0.3A	1.5A	5%					42W	4.5W
SPU45-203	+5V	0.5A	5A	5%	+24V	0.1A	1A	5%					42W	4.5W
SPU45-204	+3.3V	0.5A	5A	7%	+5V	0.2A	2A	5%					26.5W	4.5W
SPU45-209	+12V	0.3A	3A	5%					-12V	0.1A	1A	5%	42W	4.5W
SPU45-210	+15V	0.2A	2A	5%					-15V	0.1A	1A	5%	42W	4.5W
SPU45-215	+5V	0.5A	5A	5%					-24V	0.1A	1A	5%	42W	4.5W
SPU45-216	+5.1V	0A	1A	5%					+7.2V	0.2A	2.6A	5%	23.82W	4.5W
SPU45-300	+3.3V	1.0A	5A	7%	+12V	0.3A	2A	5%	-12V	0.1A	0.8A	5%	42W	4.5W
SPU45-301	+5V	0.5A	5A	5%	+12V	0.2A	2A	5%	-5V	0A	0.8A	5%	42W	4.5W
SPU45-302	+5V	0.5A	5A	5%	+12V	0.2A	2A	5%	-12V	0A	0.8A	5%	42W	4.5W
SPU45-303	+5V	0.5A	5A	5%	+15V	0.3A	2A	6%	-15V	0A	0.8A	5%	42W	4.5W
SPU45-304	+5V	0.5A	5A	5%	+24V	0.2A	1A	5%	-24V	0A	0.5A	5%	42W	4.5W
SPU45-305	+5V	0.5A	5A	5%	+24V	0.1A	1A	5%	-12V	0A	0.8A	5%	42W	4.5W
SPU45-306	+3.3V	0.5A	5A	7%	+12V	0.4A	2A	5%	-5V	0A	0.8A	5%	42W	4.5W


Mechanical Specifications:



Note:

1. Dimensions are shown in mm.
2. Weight: 535~560gs approx.
3. Optional output connector:
See page Appendix.

Derating Curve :



1. Operating Temperature: 0 to 70°C
2. Derate linearly from 100% load at 40°C to 50% load at 70°C